

Peel Force Testers provide the peace of mind to ensure taped devices are securely sealed in their pockets, yet will release at the designated force.

V-TEK's **PT-55** incorporates new technology and performance features to make setup easy, maintenance minimal, and calibration accurate. The **PT-55** can accommodate tape widths from 8 mm to 120 mm and operates at peel speeds of 120 mm to 300 mm per minute.

The **PT-55** can be ordered with an optional netbook computer/security package to allow accurate control, setup and recording, as pictured below. Using your own computer, V-TEK provides the software package required to operate the tester.



\*\*shown with optional Netbook/security package

FEATURES:

- Optional Netbook with security bracket and software for controls
- Automated home and calibration positioning
- USB communications interface
- Standard EIA peel speed of 120 mm or 300 mm per minute
- Easy design allows operator calibration in minutes
- Will handle all tape widths from 8 mm to 120 mm tape and 35.5 mm deep pocket in both punched or embossed carrier
- Measures in grams or newtons
- Customizable data fields
- Sampling rate: 100 times per second
- CE Compliant
- Dimensions: height 5" (13 cm) width 22" (56 cm) depth 10" (25 cm)
- Power required: 120/230 VAC, 50/60 Hz Weight: 22.0 lbs (10.0 Kg)



V-TEK, Incorporated  
 751 Summit Avenue  
 Mankato, MN 56001  
 (P) +1 507 387 2039  
 (F) +1 507 387 2257

[www.vtekusa.com](http://www.vtekusa.com)